

8 inch is available in different tailored packages/Spec. to perfectly meet your company's needs.

## KEY FEATURES

Android 12 GMS  
Qualcomm® Snapdrag SM4350, 2\*Kryo 460 Gold(A76) 2.0GHz + 6\*Kryo 460 Silver(A55) 1.8GHz  
Wifi6-Ready, 802.11ac, a/b/g/n, Frequency 2.4GHz/5GHz  
6GB +128GB  
5G NR: N1/N3/N28/N41/N78/N79



### ◆ Operation System

OS	Android 12 GMS
CPU	Qualcomm® Snapdrag SM4350, 2*Kryo 460 Gold(A76) 2.0GHz + 6*Kryo 460 Silver(A55) 1.8GHz
Memory	6GB +128GB
Language support	Multi-Language

### ◆ Display

Size	8" IPS HD 800*1280 500 Nits
Screen Technology	IPS Display Panel Coming® Gorilla ® Glass 3
Touch Pannel	Capacitive,10-Point Touchscreen, Glove/Wet Finger Supported

### ◆ Enclosure

Dimensions	8" 235 x 145 x 14mm (9.25 x 5.7 x 0.55 inch)
Weight	600g(21.16oz)

### ◆ Camera/Fotos/Video

Rear	13M Autofocus with Flash Light
Front	5M
Flash Lights	Support

### ◆ Keypad

8 Functions keys	Power/Home/Manu/Back/Volume +/- F1, F2
------------------	--

### ◆ Audio

Audio PA	Integrated Loudspeaker
Audio Jack	Type C

### ◆ Indicator

RBG Indicator

### ◆ Symoblogies

RFID(NFC)	Support UHF / NFC NFC Built-in: Frequency 13.56Mhz 0-3 UHF RFID modula (By Opitonal Accessories) 1D/2D Scanner modula (By Opitonal Accessories) Vehicle Charging (By Opitonal Accessories) High Precision GPS (By Opitonal Accessories)
-----------	--



### ◆ Power Source

Battery	Swappable Lithium-ion Polymer
LI-ion battery	8000mAh Rechargeable and Replaceable Lithium-ion Battery
Voltage	3.8V
Adapter	QC3.0 Quick Charge

### ◆ Battery Approvals

UN38.3 MSDS IEC 62133

### ◆ Regulatory Approvals

FCC, CE, ISED, RCM, UKCA, KC, PTCRB, GCF  
IP68  
MIL-STD-810G

### ◆ Software

Compatible with common third-party software,

### ◆ Communication

SD	1 * Micro SD Support Max:128G
SIM	2 * Nano SIM & Dual Standby
Sensors	G Sensor, Gyro., E-compass, Light Sensor
USB	USB Type C support OTG, USB 2.0
Pogo Pin	14* Back Pins Pogo Pin UART/USB/CAN/DCIN/GPIO/USB2.0
Bluetooth®	Bluetooth® 5.1
GPS	u-blox M8/ ext. GPS antenna connector GPS/GLONASS/Beidou/Galileo
Positioning Accuracy	1 m + 1PPM CEP 2.0m in SBAS
WLAN	WIFI/BT/NFC
NFC	Support UHF / NFC
Wifi	Wifi6-Ready, 802.11ac, a/b/g/n, Frequency 2.4GHz/5GHz 2G/3G/4G/5G LTE
WWAN	GSM:850/900/1800/1900 EVDO: BC0 WCDMA: B1/B2/B5/B8 TD-SCDMA:B34/B39 TDD-LTE: B38/B39/B40/B41 FDD-LTE:B1/B2/B3/B4/B5/B7/B8/B17/B20/B28 5G NR: N1/N3/N28/N41/N78/N79

### ◆ Environment

Operating temperature	-20°C~60°C(-4°F~140 °F)
Storage temperature	-30°C~70°C(-22°F~158 °F)
Relative Humidity	95% No Condensation
Drop Specification	1.5M (4.9 ft) Drop
Ingress Protection	MIL-STD-810G

### ◆ Inside the box



TAB30 device  
8000mAh Battery  
Type C charging cable  
USB QC 3.0 Power Adapter with EU, UK, US and AU

### ◆ Accessories

Handstrap  
Shoulder Strap  
Bag  
Protected Case  
Stand  
Stylus  
Micro SD Card  
Metal Cradle  
Vehicle Mounting  
Battery Charger  
Vehicle Charging by Cigarette Lighter  
Antenna