

6 inch MTK. Rugged 2D Scanner

**KEY FEATURES**

- Android 12 GMS
- ARM (5G-C) (OCTA Core)
- 5 point G+F+F capacitive touch screen
- 4GB +64GB
- G Sensor, Fingerprint
- 5.99" IPS FHD 1440\*720 350 Nits



◆ **Operation System**

OS	Android 12 GMS
CPU	ARM (5G-C) (OCTA Core)
Memory	4GB +64GB
Language support	Multi-Language

◆ **Display**

Size	5.99" IPS FHD 1440*720 350 Nits
Screen Technology	IPS Display Panel Coming® Gorilla® Glass 3
Touch Pannel	5 point G+F+F capacitive touch screen

◆ **Enclosure**

Dimensions	5.99" 80 x 164 x 14m (3.2 x 6.5 x 0.6 inch)
Weight	255g (9.0oz)

◆ **Camera/Fotos/Video**

Rear	13M OV13855 Autofocus with Flash Light
Front	5M GC5035
Flash Lights	Support

◆ **Keypad**

8 Functions keys	Power/Volume +/- / scanning
------------------	-----------------------------

◆ **Audio**

Audio PA	Built-in 8Ω/1W
Audio Jack	Type C

◆ **Symbologies**

Support UHF / NFC	NFC Built-in, Frequency 13.56Mhz 0-3 2D Scanner module built-in Zebra4710 Vehicle Charging (By Optional Accessories)
-------------------	--

◆ **Power Source**

Battery	Swappable Lithium-ion Polymer
Li-ion battery	3.8V/4500mAh Rechargeable and Replaceable Lithium-ion Battery
Voltage	3.8V
Adapter	AC100V ~ 240V

◆ **Battery Approvals**

UN38.3 MSDS IEC 62133

◆ **Regulatory Approvals**

FCC, CE, ISED, RCM, UKCA, KC, PTCRB, GCF  
IP65  
MIL-STD-810H

◆ **Software**

Compatible with common third-party software,

◆ **Communication**

SD	1 * Micro SD Support max:128G
SIM	2 * Nano SIM & Dual Standby
Sensors	G Sensor, Fingerprint
I/O	USB Type C support OTG, USB 2.0
Pogo Pin	6 * Bottom Pins Pogo Pin USD2.0/DCIN/GPIO/UART 2 * Side Pins Pogo Pin USD2.0/DCIN/GPIO/UART
Bluetooth®	Bluetooth® 5.1
GPS	GPS/GLONASS/Beidou/Galileo

WLAN	WIFI/BT/NFC
NFC	NFC Built-in, Frequency 13.56Mhz 0-3
Wifi	Wi-Fi 802.11 a/b/g/n/ac, 2.4GHz/5GHz
WWAN	GSM: 2/3/5/8 WCDMA: B1/B2/B5/B8 TDD-LTE: B38/B39/B40/B41 FDD-LTE: B1/B2/B3/B5/B7/B8/B20 5G : N1+N3+N5+N28+N38+N41+N77+N78+N79

◆ **Environment**

Operating temperature	-10°C~50°C(14°F~122 °F)
Storage temperature	-20°C~60°C(-4°F~140 °F)
Relative Humidity	95% No Condensation
Drop Specifications	1.2M (3.9 ft) Drop
Ingress Protection	MIL-STD-810H

◆ **Inside the box**



PAD60 Device  
4500mAh Battery  
AC100V ~ 240V  
USB Power Adapter with EU, UK, US and AU

◆ **Accessories**

AR Film  
Handstrap  
Bag  
Protected Case  
Stylus  
Micro SD Card  
Docking  
Vehicle Charger